



## NEW RANGE

# Indoor CATV taps and splitter 5-1000 MHz


- Zamak chassis with high-quality shielding
- Wall fixing holes
- Grounding facilities




DFC-410



DFC-415



DFC-420



DFC-425



DIFC-201

## Taps 4 outputs

MODEL			DFC-410	DFC-415	DFC-420	DFC-425
REF.			2086	2087	2088	2089
Outputs			4			
Frequency range	MHz	5-1000				
Tap loss (± 1.5 dB)		dB	10	16	20	24
Through loss	5-30 MHz	dB	≤ 3.5	≤ 1.8	≤ 1.0	≤ 1.0
	30-470 MHz		≤ 3.6	≤ 1.8	≤ 1.1	≤ 0.8
	470-1000 MHz		≤ 4.5	≤ 2.5	≤ 1.5	≤ 1.2
Directional isolation	5-30 MHz	dB	≥ 28	≥ 30	≥ 30	≥ 30
	30-470 MHz		≥ 27	≥ 28	≥ 28	≥ 28
	470-1000 MHz		≥ 25	≥ 25	≥ 25	≥ 25
Isolation between outputs	5-30 MHz	dB	≥ 30	≥ 36	≥ 40	≥ 45
	30-470 MHz		≥ 28	≥ 32	≥ 33	≥ 33
	470-1000 MHz		≥ 25	≥ 27	≥ 27	≥ 30
Return loss	5-30 MHz	dB	≥ 21	≥ 22	≥ 22	≥ 22
	30-470 MHz		≥ 20	≥ 20	≥ 20	≥ 20
	470-1000 MHz		≥ 17	≥ 17	≥ 17	≥ 17

## Splitter 2 outputs

MODEL			DIFC-201
REF.			2081
Outputs			2
Frequency range	MHz	5-1000	
Insertion loss	5-30 MHz	dB	≤ 3.5
	30-470 MHz		≤ 3.6
	470-1000 MHz		≤ 4
Output isolation	5-30 MHz	dB	≥ 30
	30-470 MHz		≥ 30
	470-1000 MHz		≥ 28
Return loss	5-30 MHz	dB	≥ 21
	30-470 MHz		≥ 21
	470-1000 MHz		≥ 20