

Technical specifications : Ref. 532210

Max. number of filters			20	
Bands		FM	VHF	UHF
Frequency range	MHz	87 ... 108	174 ... 230	470 ... 694
Channels per filter		--	--	1
Gain	dB	17	52	55
Gain adjustment range	dB	0 ... 25	AGC	AGC
Manual regulation per filter	dB	-5 ... 5	-3 ... 3	-3 ... 3
Slope regulation	dB	--	--	0 ... 5
Input level	dBmV	16 ... 41	17 ... 42	20 ... 45
Output level DIN45004B	dBmV	44	51	54
Output level EN50083	dBmV	51	58	61
Programmable output level	dBmV	10 ... 35	77 ... 102	20 ... 45
Noise figure	dB	7	6	6
Selectivity	dB	> 20	> 65	> 65
Inputs		FM	DAB	LowVHF+HighVHF+UHF
Number of inputs		1	1	2
Frequency range CHs input	MHz	87 ... 108	174 ... 230	174 ... 694
Frequency range CHs output (Off-air)	MHz	87 ... 108	174 ... 230	174 ... 694
Powering per inputs	Vdc	--	--	12
Max current input	mA	--	--	70
Input voltage	Vac		220 ... 230	
Mains frequency			50 Hz / 60 Hz	
Max. current	mA		87	
Max. power consumption	W		7.5	
Protection index (IP)			20	
Operating temperature	°F		23 ... 113	