



## CoaxData G.hn Master (Up to 64 nodes)

Turn your business' TV cable into a high-speed network

Main element of the CoaxData G.hn installation. It is responsible for the management and provisioning of the CoaxData nodes of the local Ethernet network deployed over the coax. Its typical installation is at the headend of the coaxial infrastructure, where the TV and Internet services are found.

Internally, this master is capable of managing 4 independent G.hn domains, with up to 16 nodes in each, being able to serve a total of 64 nodes in the installation (16 x 4).

Each G.hn domain uses the network 25% of the time at a rate of 425 Mbps (Total G.hn rate 1.7 Gbps / 4 domains). For greater flexibility in managing the bandwidth among the different nodes, the device features an embedded Web/CLI interface that allows the activation or deactivation of G.hn domains, among other powerful functionalities.

The master includes an intuitive embedded Web/CLI interface for professionals who want to customize the network configuration and monitor all network elements (master and nodes).

Its functionalities have been designed with the philosophy of a GPON system, so it is possible to control and act very flexibly, not only on the master, but also on the connection points of the network.

<b>Ref.</b>	769310
<b>Logical ref.</b>	COAXDATAM
<b>EAN13</b>	8424450282335

## Packaging info

<b>Box</b>	1 pcs.
------------	--------

## Physical data

<b>Net weight</b>	3,061.00 g
<b>Gross weight</b>	3,390.00 g
<b>Width</b>	332.00 mm
<b>Height</b>	189.00 mm
<b>Depth</b>	65.00 mm
<b>Main product weight</b>	2,829.00 g

## Highlights

- Plug and play: thanks to its default auto-configuration, it provides Internet access to the system as soon as it connects to the operator's router
- Highly dissipative mechanical design: its structure made of aluminum and Zamak ensures that it can withstand high temperatures even under the most adverse conditions
- Helps simplify the installation with a single coaxial output: thanks to its internal diplexer, it combines the TV headend signal with the data signal coming from the operator router for their transmission over a single cable
- Low power consumption: its easily interchangeable integrated power supply reduces power consumption by up to 19 W in the most critical scenarios
- Wall and rack mounting: its chassis is prepared for wall mounting as well as for mounting in 19" headend racks (2RU high).
- Device operation and G.hn network LED indicators
- Web/CLI embedded interface, aimed at professional experts: it allows to adjust and monitor the parameters of the G.hn network. It includes powerful functionalities similar to those of a GPON system, which facilitate the control and configuration of both the master itself and the network

nodes:

- Management of the 4 G.hn domains
- Addition/elimination of nodes in the network
- Creation of band-reject filters or notch filters
- Monitoring of the nodes' WiFi networks
- Alarms and events information
- G.hn network equipment upgrade
- Energy and temperature management