

## 912 TV-SAT AND MODULATOR EQUIPMENT

## 2XDVB-S/S2/T/T2 TO DVB-T/C TRANSMOD CI



Code: 9120253

Model: **TM-112** 

himalaya transmodulator of DVB-S/S2 satellite digital television services or DVB-T/T2 terrestrial digital television to DVB-T or DVB-C. Each module selects services from two DVB-S/S2 satellite transponders or DVB-T/T2 terrestrial channels and includes them in a DVB-T or DVB-C channel. Can be configured using a web browser in a computer conected via ethernet cable.

Equipped with a Common Interface slot for insertion of the CAM and the subscriber's card for encripted services. Can be configured using a web browser in a computer conected via ethernet cable.

CÓDIGO-CODE-CODE		9120254	9120253	9120259	
MODELO-MODEL-MODELE		TM-102	TM-112	TM-202	
ENTRADA RF / RF INPUT / ENTRÉE RF					
Número de entradas Number of inputs Nombre d´entrées		1 con desmezcla o 2 independientes 1 with duplexing or 2 independent 1 avec découplage ou 2 indépendants			
Número de receptores Number of receivers Nombre de récepteurs			2		
Rango de frecuencia Frequency range Gamme de fréquences	MHz	DVB-T/T2 : 47 - 862 DVB-S / DVB-S2 : 950 -2150			
Alimentación LNB LNB power supply Alimentation LNB	V	DiSEqC 2.0 13/18			
	mA	350			



CÓDIGO-CODE-CODE		9120254	9120253	9120259					
MODELO-MODEL-MODEL		TM-102	TM-112	TM-202					
PROCESADO TS / TS PROCESSING  Adaptación PSI/SI  PSI/SI adaptation  Adaptación PSI / SI  Adaptación NIT	G / TRAI	Generar e insertar tablas: Generation and insertion of tables: Générer et insérer des tableaux : PAT, PMT, CAT, SDT, NIT, TDT, TOT, EIT							
NIT adaptation Adaptation NIT		Sí/Yes/Oui							
Gestión de LCN, TDT, TOT LCN, TDT, TOT management Gestion LCN, TDT, TOT		Sí / Yes / Oui							
Selección de PID PID selection Sélection PID		Sí / Yes / Oui							
ACCESO CONDICIONAL / COND	ITIONAL	ACCESS / ACC	CÈS CONDITIONNEL						
Número de ranuras PCMCIA Number of PCMCIA slots Nombre d'emplacements PCMCIA		-	1	-					
Norma Standard Norme		-	DVB-CI: EN 50221 (Common Interface)	-					
Compatibilidad Compatibility Compatibilité		-	Viaccess, Mediaguard, Videoguard, Seca, Betacrypt,Nagravision, Irdeto, Crytoworks,Conax	-					
	SALIDA RF / RF OUTPUT / SORTIE RF								
Número de canales de salida Number of output channels Nombre de canaux de sortie		1 2							
Rango de frecuencia Frequency range Gamme de fréquences	MHz	DVB-T/DVB-C : 47-862							
Nivel de salida Output level Niveau de sortie	dBµV ± TOL	80 ±2,0							