

912 TV-SAT AND MODULATOR EQUIPMENT

2XDVB-S/S2/T/T2 TO DVB-T/C TRANSMOD



Code : **9120254**

Model : **TM-102**

himalaya transmodulator of DVB-S/S2 satellite digital television services or DVB-T/T2 terrestrial digital television to DVB-T or DVB-C. Each module selects services from two DVB-S/S2 satellite transponders or DVB-T/T2 terrestrial channels and includes them in a DVB-T or DVB-C channel. Can be configured using a web browser in a computer connected via ethernet cable.

| CÓDIGO-CODE-CODE | | 9120254 | 9120253 | 9120259 |
|---|-----------------|--|---------|---------|
| MODELO-MODEL-MODELE | | TM-102 | TM-112 | TM-202 |
| ENTRADA RF / RF INPUT / ENTRÉE RF | | | | |
| Número de entradas Number of inputs Nombre d'entrées | | 1 con desmezcla o 2 independientes 1 with duplexing or 2 independent 1 avec découplage ou 2 indépendants | | |
| Número de receptores Number of receivers Nombre de récepteurs | | 2 | | |
| Rango de frecuencia Frequency range Gamme de fréquences | MHz | DVB-T/T2 : 47 - 862 DVB-S / DVB-S2 : 950 -2150 | | |
| Alimentación LNB LNB power supply Alimentation LNB | V _{DC} | DiSEqC 2.0 13/18 | | |
| | mA | 350 | | |

| CÓDIGO-CODE-CODE | 9120254 | 9120253 | 9120259 |
|---------------------|---------|---------|---------|
| MODELO-MODEL-MODELE | TM-102 | TM-112 | TM-202 |

PROCESADO TS / TS PROCESSING / TRAITEMENT TS

| | | | |
|---|--|--|--|
| Adaptación PSI/SI PSI/SI adaptation Adaptation PSI / SI | | Generar e insertar tablas: Generation and insertion of tables: Générer et insérer des tableaux : PAT, PMT, CAT, SDT, NIT, TDT, TOT, EIT | |
| Adaptación NIT NIT adaptation Adaptation NIT | | Sí / Yes / Oui | |
| Gestión de LCN, TDT, TOT LCN, TDT, TOT management Gestion LCN, TDT, TOT | | Sí / Yes / Oui | |
| Selección de PID PID selection Sélection PID | | Sí / Yes / Oui | |

ACCESO CONDICIONAL / CONDITIONAL ACCESS / ACCÈS CONDITIONNEL

| | | | | |
|--|--|---|---|---|
| Número de ranuras PCMCIA Number of PCMCIA slots Nombre d'emplacements PCMCIA | | - | 1 | - |
| Norma Standard Norme | | - | DVB-CI: EN 50221 (Common Interface) | - |
| Compatibilidad Compatibility Compatibilité | | - | Viaccess, Mediaguard, Videoguard, Seca, Betacrypt, Nagravision, Irdeto, Cryptoworks, Conax | - |

SALIDA RF / RF OUTPUT / SORTIE RF

| | | | | |
|--|-------------------------|----------------------|---|---|
| Número de canales de salida Number of output channels Nombre de canaux de sortie | | | 1 | 2 |
| Rango de frecuencia Frequency range Gamme de fréquences | MHz | DVB-T/DVB-C : 47-862 | | |
| Nivel de salida Output level Niveau de sortie | dB μ V \pm TOL | 80 \pm 2,0 | | |