

# 980 COMPLETE MODULES

## ALOJ AUDIO&VIDEO PANEL 7 SIMPLE BUTTONS



Code : **9800233**

Model : **PTS-63207**

### Description

Vandal resist entrance panel for 2-wire video intercom installations. It includes the EVG-000 main module, the same one used by the USOA entrance panel. This panel has 7 call push-buttons arranged in 1 column.

### Entrance panel

- Construction in stainless steel AISI316L 2,5 mm thickness, with special vandal proof screws.
- 100% flat surface, without protrusions.
- Card holders, and camera and handicap icons front screens of 6mm thickness.
- Protection against impacts up to rate: IK09.
- IP55 protection from dust and low-pressure water jets from any direction.
- Attractive, professional and "Made in Spain" finishing.
- Handicap module with voice synthesizer with 14 selectable languages for "open door" message. It includes the possibility of mute mode.
- iACCESS optional. Comfort and distinction for owners and tenants.
- Automatic lighting of card holders in dark conditions (with LDR sensor)
- Camera with demisting system, which is activated automatically thanks to its humidity and temperature sensors.
- Greater audio power thanks to its two speakers.

| CODE                           |    | 9800233                   |
|--------------------------------|----|---------------------------|
| MODEL                          |    | PTS-63207                 |
| Dimensions                     | mm | 145 x 356                 |
| Material                       |    | AISI 316L                 |
| • Thickness                    | mm | 2,5                       |
| Compatible flush box           |    | 9740247 CMO-608           |
| • Dimensions                   | mm | 125 x 339 x 50            |
| Number of pushbuttons          |    | 7                         |
| Pushbutton Rows                |    | 7                         |
| Protection against impact rate | IK | IK09                      |
| Camera                         |    |                           |
| • Sensor                       |    | 1/3" WDR CMOS ACTIVE VIEW |
| • Lighting                     |    | White LED                 |
| • View angle                   |    | D:170° (Wide angle)       |
| "Door Opened" Message          |    | 14 Selectable languages   |
| Accessibility Indicator        |    | 4 Luminous Icons          |
| • Complying with regulations   |    | SUA-9 (CTE)               |
| iACCESS                        |    | Optional                  |
| Packing weight                 | Kg | 1,84                      |
| Packing dimensions             | mm | 170 x 485 x 80            |